

RESIDENTIAL  
& COMMERCIAL

INDUSTRIAL  
& MARINE

ART  
& CRAFT

**SHIMICOAT**  
SURFACE SOLUTIONS



# AQUAthane Tinted

## *Water-based Polyurethane*

### Description

An Industrial water based Tinted finish Polyurethane, single component sealer, designed to protect and enhance concrete surfaces internally and externally. SHIMICOAT AQUAthane Tinted is an advanced formulation, cross linking emulsion with strong bonding to well-prepared concrete surfaces. The product can be used over existing solvent based acrylic coatings to freshen up your concrete surface. AQUAthane Tinted is an odorless, Green Star compliant (VOC free) sealer.

A ready-to-use water-based Polyurethane Tinted topcoat with excellent adhesion for added scratch and mar resistance with excellent moisture barrier properties. The product is engineered for superior toughness, durability, water resistance, and is excellent for applications where hardness and longevity are required. AQUAthane Tinted is an environmentally benign, non-flammable, fast drying, low odor alternative to solvent-based lacquers.

The product can be applied to most surfaces such as:

- Driveways
- Garage & Warehouse Floors
- Cafés and restaurants
- Alfresco & Patio

### Features

AQUAthane Tinted is a single component water-based sealer designed to soak into the surface and provide protection from moisture ingress. The product's outstanding features:

- Easy Application:
  - Rolled
  - Brushed
  - Spray
- Water Based Product
- Non-Hazardous – Non-Dangerous Goods technology
- Odorless
- Weather resistance, friction resistance and compression resistance
- Hardwearing finish surface
- Excellent adhesion to concrete
- Excellent waterproof and anticorrosive properties
- Ideally suitable for under direct sunlight with extreme UV radiation
- Excellent anti-graffiti coating
- Excellent resistance to oil and most household chemicals
- Ideal for both Indoor and Outdoor
- Ready-to-use formulation without any need for dilution
- Protect against salt ion ingress
- Protect against efflorescence & biological growth
- Long lasting and Durable

 MATERIALS  CHEMICALS  RESINS  EQUIPMENT

Ph: (08) 9364 7446 | [info@shimi.com.au](mailto:info@shimi.com.au) | ABN: 28 622 871 283 | [www.shimi.com.au](http://www.shimi.com.au)

## Pack Size

Larger kit sizes are available for special orders.

Kit Size (Lt)
5Lt
10Lt
20Lt

## Colour Chart

AQUAthane Tinted is available in many colours and pre-tinted for ease of application. Standard Colours:

- White N14
- Black N61
- Neutral Grey N23
- Dark Grey N64
- Cream Y34
- Charcoal B64
- Terracotta R52
- Bright Blue B23
- Dark Brown X65

SHIMICOAT offers all Australian Standard AS2700 Colours, consisting of 206 colours. Please contact SHIMICOAT office for your custom design tint. Extra charges may apply.

## Coverage

5-10sqm/Lt Per Coat  
Recommended Two Coats

5Lt Drum Covers 25-50sqm Per Coat (Need Two Coats)  
10Lt Drum Covers 50-100sqm Per Coat (Need Two Coats)  
20Lt Drum Covers 100-200sqm Per Coat (Need Two Coats)

## Applications

Roller, Brush or Spray

## Curing Time at 25°C

Touch Dry: 6 Hours (Depending on temperature, air flow and humidity)  
Recoat: Over Night (Min 16 Hours at 25°C)  
Foot Traffic: 16 Hours  
Heavy Traffic: 72 Hours