

Silica Sand

Shimicoat Product - Technical Data Sheet



TECHNICAL DATA SHEET

1. PRODUCT DESCRIPTION

Shimicoat Silica Sand is a graded silica sand aggregate for mortars and broadcast. It is supplied as a component material for use within Shimicoat coating systems.

Product code: SS

2. TYPICAL USES

Suitable for: a graded silica sand aggregate for mortars and broadcast.

3. KEY FEATURES & BENEFITS

- Reinforces and rebuilds epoxy mortars
- Controls consistency and adds body
- Blends readily into Shimicoat resins

4. TECHNICAL PROPERTIES

This is a component material used within Shimicoat coating systems. Dosage, coverage and pack sizes vary by application.

TO CONFIRM - Pack sizes, dosage rates and physical properties are not itemised here - confirm against the live product page.

5. USE & HANDLING

- Add to / broadcast into the Shimicoat system per the relevant system instructions and at the recommended rate.
- Mix or disperse uniformly before use.

6. CLEANING

- Clean tools and uncured spills with thinner & diluent (EpoDil).

7. HEALTH, SAFETY & HANDLING

- Store out of direct sunlight and heat. Keep containers sealed.
- A Material Safety Data Sheet (SDS) is available from Shimicoat on request.

TO CONFIRM - PPE, hazard classification and shelf life are not itemised here - refer to the SDS.

8. CONTACT DETAILS & DISCLAIMER

SHIMICOAT Pty Ltd

9a Morse Road, Bibra Lake WA 6163
Ph (08) 9434 3302 info@shimi.com.au www.shimi.com.au
ABN 28 622 871 283

Disclaimer: Information herein is guidance only, based on present knowledge and experience. As use is beyond the seller's control, the product is sold without guarantees; the purchaser must conduct its own tests for suitability. Shimicoat Pty Ltd accepts no liability beyond replacement of defective product.

Source: shimi.com.au product pages (current site takes precedence).