

RESIDENTIAL
& COMMERCIAL

INDUSTRIAL
& MARINE

ART
& CRAFT

SHIMICOAT
SURFACE SOLUTIONS



Liquid Tint Colour Pigment

Applications

SHIMI COLOURS are formulated for use in most solvent based, non-aqueous industrial coatings as well as aerosols, concrete protection, general industrial finishes, industrial maintenance, marine, and protective coatings.

Usage

Tinted Epoxy: 20gr (One spoon full) to be added per liter of Epoxy Resin/Part A (1 Spoon/Lt) to cover 1sqm.

Tinted Sealer: 1Lt of Concentrated Liquid Pigment to be added to 20Lt of Acrylic Resin for 100sqm floor per coat. Dosage may increase or decrease to your desired effect.

Clean Up

SHIMICOAT Liquid Pigments are Solvent based and can be cleaned off using Xylene, EpoDil & AcryDil followed by soapy warm water wash.

Shelf Life

Proper handling is essential to maintain good quality. It is recommended that SHIMI COLOURS to be mixed prior to use. Containers should be tightly sealed when not in use. Repacking SHIMI COLOURS into a smaller container should be considered if the colorant level in the container is less than 20% of the original amount and will be stored for a extended period of time. Shelf life of SHIMI COLOURS are 3 years for most colorants and 2 years for white and oxide colorants from the date of manufacture in unopened containers.

WARNING

Keep out of reach of children

Read Safety Material Data Sheet (MSDS) of the product prior to use.

Storage

Containers should be tightly sealed when not in use. This will prevent the absorption of atmospheric moisture and minimize the chance of airborne contamination. Containers should be stored in a manner as to protect them from temperature extremes (5-50°C). Material should be mixed prior to use if stored over 30 days.

The products shall be stored out of direct sunlight and heat at all times. The shelf life of the product is 24 months.

DISCLAIMER

Material Safety Data Sheet, Technical and Environmental Data Sheet can be provided upon request.

The information provided in this document is guidance only and considering the uses of this product are beyond the seller's control, the product is sold without guarantees or warranties. Warranties and guarantees shall be governed by SHIMICOAT Standard Terms of Sale. The purchaser shall make its own tests to determine the suitability for their specific application, and Shimicoat Pty Ltd is taking no responsibility for misuse of the product. The purchaser assumes all risk of use and handling of this product. This product will be happily replaced or credited back if defective. Beyond this, Shimicoat Pty Ltd is not liable for any damages caused by this product or its use.

This information and all further technical advice are based on our present knowledge and experience.

The customer is not released from the obligation to conduct careful inspection and testing of supplied goods.



MATERIALS



CHEMICALS



RESINS



EQUIPMENT

Ph: (08) 9364 7446 | info@shimi.com.au | ABN: 28 622 871 283 | www.shimi.com.au