

RESIDENTIAL
& COMMERCIAL

INDUSTRIAL
& MARINE

ART
& CRAFT

SHIMICOAT
SURFACE SOLUTIONS



Slip Resistant Clear UVthane PLUS Complete Kit

Kit Sizes

Commercial Grade Complete Kit Slip Resistant Clear Epoxy contains:

- Crystal Clear UVthane – UV Resistant Polyurethane
- Xtra Grip SlipRes

Kit Sizes	UVthane PLUS Clear Polyurethane Resin Kit Size (Volume)	Xtra Grip SlipRes Weight
Small	1.15Lt	500gr
Medium	2.3Lt	1Kg
Large	4.6Lt	2Kg
Extra Large	12.8Lt	4Kg

Description

Slip Resistant Clear UVthane PLUS contains UV Resistant Polyurethane and Grits to install your ideal slip resistant floor for both indoor and outdoor surfaces. Slip Resistant Clear UVthane PLUS is ideal for maintaining the current look of your surface with a highly durable clear Polyurethane coating with enhanced Xtra Grip SlipRes properties. You can easily broadcast the grit over the coated surface “while wet” with another topcoat over it.

Slip Resistant Clear UVthane PLUS is an industrial grade UV Resistant Polyurethane top coating material for high performance floors with added benefit of safer surfaces. The product has various applications due to its excellent mechanical, chemical, electrical and adhesion properties to most substrates.

You can easily broadcast the grit over the coated surface “while wet” with another topcoat over it. Slip Resistant Clear UVthane PLUS is an industrial grade UV Resistant Polyurethane top coating material for high performance floors with added benefit of safer surfaces. The product has various applications due to its excellent mechanical, chemical, electrical and adhesion properties to most substrates. Two components (A & B) comes in clear, 100% solid Polyurethane with Xtra Grip SlipRes materials within its matrix. Xtra Grip Slip Resistant Clear UVthane PLUS used as Xtra Grip SlipRes coating material, with chemical resistance and durability, ideal for variety of floor coating systems in domestic, commercial and industrial capacities. Slip Resistant Clear UVthane PLUS is a high-quality solvent-less, odorless two component coating system for concrete surfaces such as driveways, pathways, workshops and warehouses providing a tough film, high gloss and wet look to protect surface from stains, spills and wear with Slip Resistance properties. Slip Resistant Clear UVthane PLUS has been developed specifically for Australian conditions using the latest surface technology. It provides excellent protection against weathering conditions and the splash and spillage of a wide range of chemicals. Slip Resistant Clear UVthane PLUS provides a highly durable, chalk resistant, wear and chemical resistance surface for concrete floors. High quality Polyurethane floor coating system that is solvent free when used as coating or binder. Clear Polyurethane coating has specially developed to be incorporated with non-slip materials to provide your desired floor finishing system, with functionality and style. The surface may be laid as a thin film using roller applicator. The thickness of the coating can be reduced by addition of Diluent.

 MATERIALS  CHEMICALS  RESINS  EQUIPMENT

Ph: (08) 9364 7446 | info@shimi.com.au | ABN: 28 622 871 283 | www.shimi.com.au

Xtra Grip SlipRes materials used in Slip Resistant Clear UVthane PLUS engineered to offer; advanced reinforcing filler functionality with many benefits such as high compressive strength, thermal resistance (high melting point), inert and chemically unreactive. Modern, hygienic, functional and economical surface.

No	Grit Size	Oil-Wet Inclining Platform Test	Wet Pendulum Test
1	Superfine	R9	P2
2	Fine	R10	P3
3	Medium	R11	P4
4	Coarse	R12	P5
5	Super Coarse	R13	P6

We DO NOT recommend using R12 and R13 as they are too coarse for this application. For Coarse and Super Coarse applications of R12 and R13, full broadcast SlipRes Xtra Grip floor shall be applied. Silica Sand can be used for full broadcast SlipRes Xtra Grip floor as it is more economical than using SlipRes Xtra Grip. Please contact SHIMICOAT office for further advice.

Features

Slip Resistant Clear UVthane PLUS is supplied in two pack kit, Part A (Resin) and Part B (Curative or Hardener). It also contains highly advanced Slip Resistant materials engineered to reinforce Polyurethane structure with added benefit of durability, high compressive strength, thermal stability and longevity. Slip Resistant Clear UVthane PLUS offers many other benefits such as:

- Improved wear and abrasion resistant
- resulting from hardness and inorganic composition of Slip Resistant materials
- Enhanced acoustic properties owing to its capacity to absorb sound and vibration within the matrix
- Improved Fire Rating performance due to its non-combustible nature and super high temperature melting point materials used in Slip Resistant Clear UVthane PLUS.
- Colour-fast and superior gloss retention due to spheres being uniformly being coated with resin and naturally rising, surfacing and positioning over the top surface
- Ideal Polyurethane Coating over the spheres' outer layer, due to the surface tension.
- Modern, Hygiene, Functional and Economical.
- Safe and Compliance with most regulatory.
- Heavy duty clear or pigmented coating for concrete and polished concrete floors.
- Highly resistant to chemical attack and pedestrian or vehicular traffic.
- Long lasting and easily maintained with good resistance to a wide range of domestic and commercial chemicals.
- Solvent free when used as a clear unpigmented coating or binder.
- Outstanding water resistance.
- Seamless, easy to clean and maintain.
- Superior Chemical Resistant Finished surface
- Solvent Free (Unless you apply Diluent for thickness control)
- Engineered formulation for trafficable area with high mechanical strength
- DIY Friendly, easy to apply and curable over a wide range of temperature

Colour Chart

Clear & Transparent - Water Clear to Pale Amber.

Coverage

1L covers approximately 5sqm per coat, depend on the conditions of the surface.
First coat usually consumes more and the second coat less.

Applications

Roller, Brush or Squeegee.

Dry Time at 25°C

Pot Life:	45 minutes at 25°C
Tack Free:	2-3 hours
Thin Film Set:	6 Hours (Min, depending on temperature and humidity)
Dry Cured:	8-16 hours – Foot Traffic (depending on temperature and humidity)
Fully Cured:	7 days (Vehicle Traffic)
Re-Coat:	Over night