

RESIDENTIAL
& COMMERCIAL

INDUSTRIAL
& MARINE

ART
& CRAFT

SHIMICOAT
SURFACE SOLUTIONS



Metallic Pearlescent Pigment *Paste Liquid*

Pack Sizes

Pack Size (mL)
200mL
1Lt

Colour Chart

You can choose any combination for your metallic colour finish. We recommend choosing lighter colours such as Pearl White, Silver Frost, Milky Marble as main colour and any other colours as feature/contrast colour.

If you wish to get darker surface, you may choose Gun Metal which provides smoky black appearance.

- Copper Cup
- Dragon Gold
- Flame Red
- Forest Green
- Grass Green
- Gun Metal
- Lime Green
- Pink Perfect
- Royal Blue
- Coffee Club
- Silver Frost
- Vibrant Purple
- Wild Orange
- Pearl White
- Milky Marble
- Metallic Yellow
- Top Teal
- Turquoise
- Cobalt Aqua

Usage

20mL (One spoon full) to be added per liter of Epoxy Resin/Part A (1 Spoon/Lt) to cover 1sqm.

Dosage may increase or decrease to your desired effect.

Applications

Add liquid pearlescent pigment into the resin (Part A), mix well followed by adding Part B into the resin blend. Apply to the surface in your desired method:

1. Pour On and squeegee to spread over the surface
2. Roll On using a Roller
3. Brush On using a Brush

 MATERIALS  CHEMICALS  RESINS  EQUIPMENT

Ph: (08) 9364 7446 | info@shimi.com.au | ABN: 28 622 871 283 | www.shimi.com.au

Description

SHIMICOAT Metallic Pearlescent Pigments For Special Effect Resurfacing Systems

SHIMICOAT Metallic Pearlescent Pigments are special effect pigments composed of mica nano-particles coated with various inorganic pigments to create metallic effects that mimic the natural look of stone and rock formations. These unique pigments are designed to be blended with SHIMICOAT 100% solids clear Epoxy resins. When the metallic particles are mixed with epoxy, they give the coating a shine that reflects light and creates eye-catching dramatic effects.

Metallic Pearl Liquid Pigments in Epoxy:

Metallic Pearlescent Pigments are commonly used in epoxy coating systems as the mid coat (second coat) over the primer/basecoat Epoxy. Your metallic pigments should be mixed with clear epoxy and installed over an epoxy tinted base coat. The most popular basecoats are Gun Metal and Pearl White.

Typically, people use black for base coat. If you're just using the metallic Liquid pigments in a clear coat you need to put your coating on much thicker than normal rolling or brushing, in order to cover and achieve the desirable color. We normally recommend 500-1000micron Clear Topcoat, which consumes 500mL to 1Lt per sqm of resin. For example, 200mL container shall be added into 15 Liter of 100% solids epoxy to be enough for 15sqm of coverage of rich 1000 μ per sqm. Metallic Pearlescent Liquid Pigment can be used in floor coating, countertop resurfacing, wall paints, plastic molding, ink applications, arts and crafts. Always test your method of use before applying to your entire project.

SHIMICOAT Metallic Liquid Tint being used globally to create unique stunning Polyurethane & Epoxy Resin designs. It is a great fun to play with these pigments and create your own unique and exotic colour combinations. Using our Pigments, you will be guaranteed; Non-bleed or Fading, Non-Rust or Toxic, Vegan & Cruelty Free, Food and Drug Administration (FDA) compliance and temperature resistance so can be used for worktops and floors with underfloor heating. Shimicoat Metallic Liquid Tint mix well with any clear epoxy and disperse rapidly.

The finished surface is a designer high gloss appearance with subtle reflective sparkle. Very unique and impossible to replicate two floors exactly the same. There are endless creative and stunning techniques and finish surface that you can call your own.

Composition of SHIMICOAT Metallic Liquid Tint

SHIMICOAT Metallic Liquid Tint contain the following mineral and inorganic compounds at different ratios for various colours and effects:

1. Mica "Potassium Aluminum Silicate (PAS)"
2. Titanium Dioxide (TiO₂)
3. Selenium Dioxide (SnO₂)
4. Ferric Iron Oxide (Fe₂O)

It contains 100% naturally occurring inorganic compounds in Epoxy Resin Matrix.

SHIMICOAT Pearlescent Pigment Liquids are composed of above metal oxide layers of moldy mica in epoxy resin matrix. Pearl pigments change the thin layer of metal oxide to produce different pearlescent effects. Compared with other pigments, pearlescent pigments have an unparalleled effect on the unique soft pearl luster. The special surface structure, high refractive index and good transparency make it the same effect as pearl in a transparent medium. The excellent chemical and high temperature resistance of pearlescent pigments offers its potential for wide application in coatings, inks, plastics and many other fields. They provide a new color system and color quality for these products.

SHIMICOAT Pearlescent pigments are low/nil in heavy metal and meet the safety standards to be used in many commercial and domestic applications. Both acid and alkali cannot attack pearlescent pigment at room temperature. SHIMICOAT Pearlescent Pigment cannot burn, is not self-igniting, is not conductive, and can withstand high temperatures of up to 140°C (284°F). Pearlescent pigments can also be used in reactive coatings for radiation curing systems (electron multiply curing, photocuring).

SHIMICOAT Metallic Liquid Tint are one of our most versatile products that can be used to create your desirable metallic or pearlescent effect in many resin systems. The product may be used in acrylics, oils, printing inks, encaustics, alcohol inks, epoxy, glues, casting resins, clay, varnishes, etc.

Pearlescent Pigments are safe, inert pigment that exhibits extreme colorfastness and stability. The different particle sizes produce different effects, from a smooth pearly luster, to a highly metallic sheen. The product creates a metallic effect without being a real metal—it will never tarnish or fade!

Note: SHIMICOAT Pearlescent Pigment Liquids are specifically engineered for art/craft materials, surface coating and industrial applications.

SHIMICOAT Metallic Liquid Tint are ideal for Translucent Effect. The product can be used in many coating applications in bars, clubs, retail stores, residential interior floors and showrooms. For further information, please refer to SHIMICOAT website or contact one of our sales and technical team.

Features

- 100% naturally occurring inorganic compounds.
- Widely used in epoxy, acrylic and many other resins.
- Pearlescent pigments are also used in epoxy paint, art and craft, industrial coating applications.
- Quality pearl pigments are easily dispersible into transparent paint.
- Required dosage of only 1%-2%.
- Rapidly disperses into your liquid system.
- Easy roll, brush or pour-on application.
- Great modern colour choices.
- Provides a beautiful three-dimensional appearance
- Unique in design offering the illusion of ripples, craters and swirl.

Specifications

SHIMICOAT Pearl Luster Metallic Pigment contains Mica and Titanium Dioxide. Both components are naturally occurring inorganic compounds:

Attribute	Properties
CAS No	12001-26-2 and 1309-37-1
Formula	Mica and Titanium Dioxide in Bed of Epoxy
Colour	Available in many colours
Appearance	Superfine easily dispersible Liquid
Applications	Epoxy Coating, Art & Craft, Industrial Coating Systems
Density	1.4g/mL (1.4gr/cm ³)
Other Properties	Chemical Resistant - Water Resistance -Heat Resistance - UV Resistant -Non-toxic

Direction

Mixing

NOTE: The mix procedures below are indicative guidelines/suggested proportions only. Adjustments can be made based on your personal preference/application. Always use a test piece first.

Epoxy Coating Applications:

Epoxy Coating Applications - Usage	Grams Per Litre
Solid Pearls - Ghost Pearls - Nebula Pearls	15-25 g/Lt
Colour-Shift & Chameleon Pearls	20-50 g/Lt
Glow in the Dark Pigments	50 g/Lt
Micro Flakes & Glitters - Holographic Micro Flake	5 g/Lt

Clean Up

The product is dusty, handle carefully and wipe off the surfaces once finished. Use thinner & Diluent (Blend of Solvents) to remove colour stains.

WARNING

Keep out of reach of children

Read Safety Material Data Sheet (MSDS) of the product prior to use.

Storage

The products shall be stored out of direct sunlight and heat at all times. The shelf life of the product is 24 months.

DISCLAIMER

Material Safety Data Sheet, Technical and Environmental Data Sheet can be provided upon request.

The information provided in this document is guidance only and considering the uses of this product are beyond the seller's control, the product is sold without guarantees or warranties. Warranties and guarantees shall be governed by SHIMICOAT Standard Terms of Sale. The purchaser shall make its own tests to determine the suitability for their specific application, and Shimicoat Pty Ltd is taking no responsibility for misuse of the product. The purchaser assumes all risk of use and handling of this product. This product will be happily replaced or credited back if defective. Beyond this, Shimicoat Pty Ltd is not liable for any damages caused by this product or its use.

This information and all further technical advice are based on our present knowledge and experience.

The customer is not released from the obligation to conduct careful inspection and testing of supplied goods.